


Instrument Approach Chart
(IAC) - ICAO

AD ELEV 1417ft

TRANSITION LEVEL by ATC
TRANSITION ALTITUDE 7000ZURICH LSZH
ILS RWY 28

MISSED APPROACH

Initial climb clearance 4000.

Climb straight ahead. At D2.5 IZW past the station turn left (MAX IAS 210kt) on TR193. When established on TR193 continue climb to 7000. Intercept R061 to WIL. At D10.0 WIL to the station turn right. Establish TR328 to intercept R013 from WIL. Proceed to GIPOL. MNM climb gradient 4.5% up to 6000 due to ASP restrictions.

ELEV 1416
THR RWY28

IZW DME

D3.3 IZW

RAMEM (FAP)

D10.3 IZW

ILS RDH 51

DME reads D0.2
IZW at THRMissed APCH climb
gradient requirement

STRAIGHT-IN APPROACH

gradient requirement		STRAIGHT-IN APPROACH				
		A	B	C	D	D _L
		OBSTACLE CLEARANCE ALTITUDE (HEIGHT)				
2.5%	pressure altimeter	2270 (854)	2280 (864)	2293 (877)	2303 (887)	
4.0% to 2700		2069 (653)	2079 (663)	2092 (676)	2102 (686)	
		DECISION ALTITUDE (HEIGHT)				
2.5%	pressure altimeter	2270 (854)	2280 (864)	2293 (877)	2303 (887)	
4.0% to 2700		2091 (675)	2091 (675)	2092 (676)	2102 (686)	

CAUTION

- Do not confuse RWY 32 with RWY 28.
- Bright floodlight slightly N of APCH at D0.7 IZW.
- Expect turbulences on short final during south-westerly winds.
- Nuisance GPWS glideslope warning may be expected below 100ft THR.
- 0.4NM BFR THR28 visual segment surface (VSS) penetrated by trees up to 1496ft AMSL.

REMARK

- Uncategorised ILS APCH RWY 28 due to obstacle limitation and restriction according to non-instrument RWY criteria.
- ILS 28 signal fulfils ICAO Annex 10, CAT I specifications.

ROD	GS kt	90	110	130	150
	FT/MIN	526	642	759	876

COR: completely revised (WEF 02DEC2021)

THIS PAGE INTENTIONALLY LEFT BLANK