



Instrument Approach Chart
(IAC) - ICAO

AD ELEV 1675ft

TRANSITION LEVEL by ATC
TRANSITION ALTITUDE 6000BERN-BELP LSZB
ILS RWY 14
HELICOPTER CAT H

Missed APCH climb gradient requirement		STRAIGHT-IN APPROACH						
		OBSTACLE CLEARANCE ALTITUDE (HEIGHT)						
		H						
4.2%	pressure altimeter	2334 (666)						
5.0% up to 3100		2229 (561)						
7.0% up to 3100		2075 (407)						
		DECISION ALTITUDE (HEIGHT)						
4.2%	pressure altimeter	2334 (666)						
5.0% up to 3100		2229 (561)						
7.0% up to 3100		2117 (449)						
ROD	GS kt	90	110	130	140			
	FT/MIN	637	779	920	991			

CAUTION

- MAX GS 140kt in final APCH to avoid ROD >1000ft/min.
- 0.7 NM BFR THR 14 Visual Segment Surface (VSS) penetrated by trees up to 1890ft AMSL.
- This is not a standard APCH angle.

REMARK

- Uncategorised ILS APCH RWY 14 due to OBST limitation and restriction according to non-instrument RWY criteria.
- ILS14 signal fulfills ICAO Annex 10, CAT I specifications.
- Circling according to specific APCH charts.

COR: DA(H) 7.0% value changed, REMARK note (WEF 25FEB2021)

THIS PAGE INTENTIONALLY LEFT BLANK