



GP/DME/VDF
GP shelter located next to GP antenna

For OBST see AIP LSGG AD 2.10

Touchdown 22
single engine ACFT

LEGEND/RMK

Arrivals:
PSN equipped with/without visual docking guidance system → LSGG AD 2.9
The appropriate stop line - 1, 2 or 3 - at the ACFT stand will be transmitted by Geneva APRON.

TWY LGT	Apron area, RWY-Exits, TWY curves
EDGE	A, B, D, E, G, OUTER, INNER, LINK 0, 1, 2, 3, 4, 5 and HLDG bays A and G
CL	B, D and E
RETIL	A*, B, C, D, E, F, G*, Y, Z - *Across TWY
RLG	

Departures:
Push back procedure → LSGG AD 2.20

ATIS	135.580
DEL	121.680
APRON SOUTH	121.855
TWR	118.700

TWY:
 — Guideline for taxiing
 — HLDG position CAT I
 — Stop bar LGT CAT II-III H24
 ○ RWY guard LGT

Taxiways:
 On apron, wing tip clearance is provided only if ACFT main gear center remains over the guidelines.
 The TWY system south of the RWY fulfills ACFT code letter E operations (MAX wing span 65.0 m).
 Exceptions and particularities are listed → AD 2.8 § 5.

THIS PAGE INTENTIONALLY LEFT BLANK