



Instrument Approach Chart
(IAC) - ICAO

AD ELEV 1411ft

TRANSITION LEVEL by ATC
TRANSITION ALTITUDE 7000GENEVA LSGG
ILS RWY 22
CAT II & CAT III

OBSTACLE CLEARANCE ALTITUDE (HEIGHT) ¹⁾				
Missed APCH climb gradient requirement				
CAT I	pressure altimeter	2.5%	A	B
			2420 (1055)	2430 (1065)
CAT I	pressure altimeter		C	D
			2440 (1075)	2450 (1085)
CAT I	radio altimeter	4.2% to 4800	A	B
			1530 (165)	1538 (173)
CAT II	radio altimeter and autopilot		C	D
			1432 (67)	1438 (73)
			1427 (62)	1436 (71)
DECISION ALTITUDE (HEIGHT) ¹⁾				
CAT I	pressure ²⁾		A	B
			1565 (200)	
CAT II	radio altimeter and autopilot ²⁾		C	D
			1465 (100)	
Circling ^{3) 4)}				
			2100 (689)	2150 (739)
			2400 (989)	

DIST DME ISW	2	4	6	8	8.3	10	12	14	16
recommended CROSSING ALT	2000	2640	3280	3910	4000	4550	5190	5820	6460

ROD	GS kt	90	110	130	150
	FT/MIN	478	584	690	796

NOTE¹⁾ Above THR elevation 1365ft.²⁾ Radio altimeter reading at CAT I DH 216ft, at CAT II DH 108ft, for lower operating minima (DH and RVR) PPR FOCA.³⁾ Above aerodrome ELEV 1411ft, circling on request of ATC under special conditions and north of RWY only, speed (MAX IAS 180kt) and radius for category D as for category C aircraft.⁴⁾ Circling must remain inside CTR at all times.

COR: completely revised (WEF 31OCT2024)

THIS PAGE INTENTIONALLY LEFT BLANK