





PSN W
TWY T (Blue and Orange): ACFT only with marshaller or tow and BTN sunrise to sunset only.
Handling allowed on stand W52 and W54 only.
All parking PSN W: Outbound with push-back only.

APRON SOUTH



For sequencing - ACFT South of RWY 10-28 with TAKE OFF RWY 28 will initially be cleared to the intermediate HLDG PSN A2, P1, P2 or Y1


LEGEND

- Guideline for taxiing
- Intermediate HLDG PSN
- Intermediate HLDG PSN with Stop bar
- RWY GUARD LGT

- Stop bar CAT I
- Stop bar LGT CAT I H24
- Stop bar LGT CAT II-III
- Stop bar LGT CAT I-II-III H24

- Blast fences
- Light pole

ACFT PRKG:



STOP Marking:
ACFT has to be stopped with the pilot seat ABM the stop line.
Stop line is visible from the left-hand pilot seat only.

GENERAL REMARKS

- On apron wing tip clearance is provided only if ACFT main gear centre remains over the guidelines
- TWY A and TWY B: DRG ILS APCH RWY 28, TWY A and TWY B BTN TWY K and THR 28 CLSD to ACFT with wingspan equal or greater than 36 m
- TWY E BTN G01 and G06: ICAO Code C ACFT only up to 36 m wingspan
- TWY F from TWY-N to TWY-M: ICAO Code C ACFT only up to 36 m wingspan
- TWY P: ICAO Code C ACFT only up to 36 m wingspan
- TWY S: MAX 30 m wingspan, with marshaller MAX 31 m
- TWY Z: Outer main gear wheel span MAX 6 m. MAX 30 m wingspan



ACFT taxiing on TWY E, F, J or K:
Be aware of RWY AHEAD
ACFT taxiing to RWY28:
Be aware of sharp turn from TWY E or F onto TWY A
For LDG RWY 34: TWY E6 only available as RWY exit with prior ATC clearance
For LDG RWY 28: TWY F to the south only available as RWY exit with prior ATC clearance

THIS PAGE INTENTIONALLY LEFT BLANK