

SAMEDAN (LSZS)
RNAV high performance RWY 03

MSA LSZS ARP
Circle: 25 NM

RONAG HLDG
INBD 146° (149.1°T),
1min, MAX IAS 210kt;
14000 - FL190

RONAG 14000

RNAV 1
GNSS required

IRS required (if no IRS, ceiling MNM 2000ft above AD ELEV)

COMMUNICATION FAILURE PROCEDURE:

- Set transponder on 7600.
- Enter RONAG HLDG at MNM 14000ft.
- Perform two HLDG pattern.
- If radio contact is not re-established, proceed to DEST according FPL

CAUTION: Procedure partly within airspace class E and G. VFR Traffic without radio communication and without transponder must be expected. Airspace class E up to FL150 (FL130 during MIL ON).

SPEED LIMITATION, GENERAL:
MAX IAS 210kt.

CLOSE-IN OBST: Right of track up to 5715ft shortly after end of RWY 03 (REF AIP LSZS AD 2.10).

DER03
SAMEDAN LSZS

ZS500

ZS710

RONAG 14000

VAR 3° E 2019.5

BEARINGS, TRACKS AND RADIALS ARE MAGNETIC
DISTANCES IN NM
ALTITUDES IN FT

ITALY
SWITZERLAND

0 5 10 NM
0 5 10 KM

9° 45'
46° 30'
10° 00'
10° 15'
10° 30'

9° 45'
46° 30'
10° 00'
10° 15'
10° 30'

COR: chart renaming, PBN box (WEE 20FEB2025)

THIS PAGE INTENTIONALLY LEFT BLANK