

ZURICH (LSZH)
RNAV RWY 14

COMMUNICATION FAILURE PROCEDURE:
SET TRANSPONDER TO CODE 7600.

- After reception of a transition CLR: continue FLT according to the published profile of the PROC with subsequent final APCH of a published instrument approach PROC.
- After reception of a CLR direct to a WPT on a transition: continue FLT direct to the cleared WPT, rejoin transition according to the published profile of the PROC with subsequent final APCH of a published instrument approach PROC.
- When being radar vectored to a WPT on a transition: resume own navigation to rejoin transition in the most direct way and proceed according to the published profile of the PROC with subsequent final APCH of a published instrument approach PROC.

CLEARANCE PHRASEOLOGY:

- "CLEARED XXX TRANSITION":
Authorization to fly the lateral RNAV 1-Route.
Level assignments will be issued by ATC.
- "CLEARED DIRECT WAYPOINT XXX":
Authorization to fly from the present position direct to a waypoint and to join thereafter the appropriate RNAV 1-Route.
Level assignments will be issued by ATC.

MSA LSZH ARP
Outer Circle: 25 NM
Inner Circle: 17 NM

RNAV 1
GNSS or DME/DME required

SPEED LIMITATION:
Below FL100 MAX IAS 250kt.

If unable to follow transition advise ATC immediately: "unable RNAV transition!"

RILAX 14 and AMIKI 14: DME TRA required for DME/DME navigation.

AMIKI HLDG
INBD 274° (271.1°T)
1min, MAX IAS 230kt;
7000 - FL240

GIPOL HLDG
INBD 077° (080.3°T)
1min, MAX IAS 230kt;
7000 - FL240

DONAUESCHINGEN-VILLINGEN EDTD
RILAX
INBD 188° (191.3°T)
1min;
7000 - FL240

ZURICH LSZH
KLO
DVOR 114.85

DÜBENDORF LSMD

OSNEM (FAF/FAP)
4000

TMA ZÜRICH

CTA ZÜRICH

GERMANY

SWITZERLAND

Scale: 0 5 10 15 20 KM / 0 5 10 NM

COOR: CTR & TMA LSZH, chart renaming, PBN box (WIEF 20MAR2025)

THIS PAGE INTENTIONALLY LEFT BLANK