

GENEVA (LSGG)
RNAV RWY 22

COMMUNICATION FAILURE PROCEDURE:

- Set transponder on code 7600.
- If on final intercept or cleared for the approach, continue as instructed and follow the IAC.
- In any other case, proceed direct to GEVEVA at last assigned and acknowledged FL.
- When in the GEVEVA HLDG pattern descend or climb to FL100.
- If RWY 04 is in use, leave GEVEVA HLDG at FL100 and proceed via PITOM, GG502 (MAX IAS 220kt) to INDIS and carry out an instrument approach according to IAC.
- Cross PITOM at or above FL080, GG502 at or above 7000.
- If RWY 22 is in use, leave GEVEVA HLDG at FL100 and proceed via GG525, GG512 (MAX IAS 220kt) to SAPRE and carry out an instrument approach according to IAC.
- Cross GG525 at or above FL080, GG512 at or above 7000.
- For ACFT equipped with onboard telephone, dial +41 22 798 7600 and mention last RTF channel used.

SPEED LIMITATION, GENERAL:
Below FL100 MAX IAS 250kt or as requested by ATC.

RNAV 1
GNSS or DME/DME/IRU required.

MSA LSGG ARP
Outer Circle: 25 NM
Inner Circle: 10 NM

BEARINGS, TRACKS AND RADIALS ARE MAGNETIC DISTANCES IN NM ALTITUDES MFT

VAR 3° E 2024.5

Scale: 0 5 10 15 20 KM / 0 5 10 NM

Geographical Labels: FRANCE, SWITZERLAND, ITALY, LAKE GENÈVE, TMA GENEVA, ANNECY-MEYTHET LFLP, INDIS, CBY, RILTI, BELUS, BANKO 3R, KINES 2R, VALBU, SUVEL, BIVLO, PITOM, GENEVA LSGG, GEVEVA, SAPRE, BEUS 3R, KINES 2R, ROCCA, GG519, KINES, BANKO 3R, GG520, VALBU, SUVEL, BIVLO, PITOM, GENEVA LSGG, GEVEVA, SAPRE, BEUS 3R, KINES 2R, ROCCA, GG519, KINES, BANKO 3R, GG520.

Holding Patterns:
- SAPRE HLDG: INBD 223° (225.6°T); 1min; MAX IAS 210kt at 8000 or below, 230kt above 8000; 7000 - FL230.
- GEVEVA HLDG: INBD 205° (208.1°T); 1min; MAX IAS 230kt; 7000 - FL150.
- GOLEB HLDG: Overload HLDG on ATC REQ only; INBD 346° (349.3°T); 1min; MAX IAS 250kt; FL200 (FL180 by ATC) - FL240.
- CBY HLDG: Overload HLDG on ATC REQ only; INBD 026° (029.0°T); 1min; MAX IAS 220kt; FL100 - FL140.

Navigation Aids:
- GENEVA LSGG: VOR 115.40 MHz, 7000 - FL150.
- ANNEXY MEYTHET LFLP: VOR 115.40 MHz, 7000 - FL150.

Other Information:
- NOT TO SCALE: Several areas of the chart are labeled "NOT TO SCALE".
- COH: chart renaming, PRN box (WLF-20(FRBR2025))

THIS PAGE INTENTIONALLY LEFT BLANK